



Converging  
Innovations



Expanding  
Solutions



Price List 2026



Solution for  
Metering & Protection

## ELT

### Tape Insulated Rectangular Type Current Transformers



Ratio	Inner Diameter	Outer Diameter	CAT No.	Class 1	
				VA	List Price
800/5	105X60	140X105	ELTA	15	800
1000/5	105X60	140X105	ELTA	10	910
	105X60	140X105	ELTA	15	930
1250/5	105X60	150X110	ELTI	15	1115
1600/5	105X60	150X110	ELTI	10	975
	105X60	150X110	ELTI	15	1350
2000/5	105X60	150X110	ELTI	10	1360
	105X60	150X110	ELTI	15	1450
2500/5	130X60	170X110	ELTB	15	1475
	130X60	170X110	ELTB	15	1625
	170X85	245X160	ELTE	15	1725
3200/5	170X85	245X160	ELTE	15	2100
4000/5	170X85	245X145	ELTN	15	2585
5000/5	170X85	245X145	ELTN	15	3350

Ratio	Inner Diameter	CAT No.	INRs - List Price		
			Class 1		
			5VA	10VA	15VA
100/5	30	EOT30	675	1100	1410
	40	EOT40	675	1100	2200
125/5	30	EOT30	500	800	1025
	40	EOT40	600	750	1400
150/5	30	EOT30	425	600	780
	40	EOT40	500	700	1180
160/5	30	EOT30	450	600	790
	40	EOT40	425	750	1075
200/5	30	EOT30	425	600	675
	40	EOT40	425	550	650
	55	EOT55	485	685	800
250/5	40	EOT40	425	550	630
	55	EOT55	425	625	800
300/5	40	EOT40	425	520	580
	55	EOT55	525	600	650
400/5	40	EOT40	430	550	610
	55	EOT55	460	525	650
500/5	55	EOT55	410	560	675
600/5	55	EOT55	525	550	775
	70	EOT70	550	650	750
800/5	70	EOT70	700	750	950
	90	EOT90	530	860	965
1000/5	90	EOT90	-	925	1050
	110	EOT110	-	775	1025
1200/5	110	EOT110	-	875	925
	90	EOT90	-	940	1065
1250/5	110	EOT110	-	950	1100
	130	EOT130	-	1110	1110
1600/5	110	EOT110	-	1125	1325
	130	EOT130	-	950	1100
2000/5	110	EOT110	-	-	1500
	130	EOT130	-	-	1125
	140	EOT140	-	-	1430

## EOT

### Tape Insulated Ring Type Current Transformers



Ratio	Inner Diameter	CAT No.	INRs - List Price					
			1.5VA		2.5VA		5 VA	
			Class 5	Class 1	Class 5	Class 1	Class 5	Class 1
25/5	30	EOT30	500	-	-	-	-	-
30/5	30	EOT30	425	540	-	-	-	-
40/5	30	EOT30	-	450	-	-	-	-
50/5	30	EOT30	-	410	1100	-	-	-
60/5	30	EOT30	-	425	850	-	-	-
75/5	30	EOT30	-	-	-	425	-	775
80/5	30	EOT30	-	-	-	-	-	775
100/5	30	EOT30	-	-	-	350	425	675

#### Note

- 1) Axial depth shall vary with reference to Class of Accuracy.
- 2) Standard Lead length shall be 100 mm with 2.5 sq.mm. Ring type lug.
- 3) Mounting clamp can be provided on request on chargeable basis.



**Elmex Controls Pvt. Ltd. | Elmex Electric Pvt. Ltd.**

12, GIDC Estate, Makarpura, Vadodara -390010, Gujarat, India

☎ 0265-2642021 / 23

✉ marketing@elmex.net

🌐 www.elmex.net



Scan for Website



[in](#) ElmexControls | [f](#) ElmexControls | [X](#) ElmexControls | [@](#) ElmexControls | [v](#) ElmexControls

TECHNICAL SPECIFICATIONS MAY CHANGE IN LINE WITH TECHNICAL ADVANCES AND INDUSTRY STANDARDS.